APTU Uniform Rules (Appendix F to COTIF 1999) **Uniform Technical Prescriptions (UTP) General Provisions** –

ESSENTIAL REQUIREMENTS

Explanatory note:

The texts of this UTP which appear across two columns are identical to corresponding texts of the European Union regulations. Texts which appear in two columns differ; the left-hand column contains the UTP regulations, the right-hand column shows the text in the corresponding EU regulations. The text in the right-hand column is for information only and is not part of the OTIF regulations.

OTIF UTP

Corresponding text in EU regulations 1

EU ref.

INTRODUCTION

In order to ensure the interoperability and safety of the COTIF rail system, the essential requirement specified in this UTP must be met by the subsystems, the interoperability constituents and the interfaces.

The provisions set out in the UTPs and the annexes to them, must specify the essential requirements relevant to the subject, including the interfaces to other subjects.

"Essential requirements" means all the Def. conditions set out in Annex III (to the Interoperability Directive) which must be met by the rail system, the subsystems, and the interoperability constituents, including interfaces.

If certain technical aspects corresponding to the essential requirements cannot be Art 5, explicitly covered in 6.

a UTP, a TSI,

they shall be clearly identified in an annex to the

UTP TS

as open points.

1. GENERAL REQUIREMENTS

Annex

1.1 Safety

- 1.1.1 The design, construction or assembly, maintenance and monitoring of safety-critical components, and more particularly of the components involved in train movements must be such as to guarantee safety at the level corresponding to the aims laid down for the network, including those for specific degraded situations.
- 1.1.2 The parameters involved in the wheel/rail contact must meet the stability requirements needed in order to guarantee safe movement at the maximum authorised speed. The parameters of brake equipment must guarantee that it is possible to stop within a given brake distance at the maximum authorised speed.
- 1.1.3 The components used must withstand any normal or exceptional stresses that have been specified during their period in service. The safety repercussions of any accidental

¹ Interoperability Directive 2008/57/EC, published in the EU Official Journal L191 on 18.07.2008.



UTP GEN-A Page 2 of 7

Status: IN FORCE

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Date: 01.12.2011

OTIF UTP

Corresponding text in EU regulations 1

EU ref.

failures must be limited by appropriate means.

1.1.4 The design of

fixed installations and

rolling stock and the choice of the materials used must be aimed at limiting the generation, propagation and effects of fire and smoke in the event of a fire.

1.1.5 Any devices intended to be handled by users must be so designed as not to impair the safe operation of the devices or the health and safety of users if used in a foreseeable manner, albeit not in accordance with the posted instructions.

1.2 Reliability and availability

The monitoring and maintenance of fixed or movable components that are involved in train movements must be organised, carried out and quantified in such a manner as to maintain their operation under the intended conditions.

1.3 Health

1.4.2

1.3.1 Materials likely, by virtue of the way they are used, to constitute a health hazard to those having access to them must not be used in trains

and railway infrastructures.

1.3.2 Those materials must be selected, deployed and used in such a way as to restrict the emission of harmful and dangerous fumes or gases, particularly in the event of fire.

1.4 Environmental protection

1.4.1 The environmental impact of establishment and operation of the rail system must be assessed and taken into account at the design stage of the system in accordance with the

Community

provisions in force

in the State of application.

The materials used in the trains

and infrastructures

must prevent the emission of fumes or gases which are harmful and dangerous to the environment, particularly in the event of fire.

- 1.4.3 The rolling stock and energy-supply systems must be designed and manufactured in such a way as to be electromagnetically compatible with the installations, equipment and public or private networks with which they might interfere.
- 1.4.4 Operation of the rail system must respect existing regulations on noise pollution.
- 1.4.5 Operation of the rail system must not give rise to an inadmissible level of ground vibrations for the activities and areas close to the infrastructure and in a normal state of maintenance.



UTP GEN-A Page 3 of 7

Status: IN FORCE

OTIF UTP

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Corresponding text in EU regulations 1

Date: 01.12.2011

EU ref.

1.5 Technical compatibility

The technical characteristics of the infrastructure and fixed installations must be compatible with each other and with those of the trains to be used on the rail system.

If compliance with these characteristics proves difficult on certain sections of the network, temporary solutions, which ensure compatibility in the future, may be implemented.

2. REQUIREMENTS SPECIFIC TO EACH SUBSYSTEM

2.1 Infrastructure

As COTIF concerns infrastructure only to the extent related to interfaces with the vehicles and other movable railway material, there are no further essential requirements to infrastructure than those indicated in the General Requirements indicated in Chapter 1 above.

2.1.1 Safety

Appropriate steps must be taken to prevent access to or undesirable intrusions into installations.

Steps must be taken to limit the dangers to which persons are exposed, particularly when trains pass through stations.

Infrastructure to which the public has access must be designed and made in such a way as to limit any human safety hazards (stability, fire, access, evacuation, platforms, etc.).

Appropriate provisions must be laid down to take account of the particular safety conditions in very long tunnels and viaducts.

2.2 Energy

COTIF concerns the energy-supply systems in relation to the vehicles and other movable railway materials; the fixed installations are only concerned in relation to their interfaces with the rolling stock.

2.2.1 Safety

Operation of the energy-supply systems must not impair the safety either of trains or of persons (users, operating staff, trackside dwellers and third parties).

2.2.2 Environmental protection

The functioning of the electrical or thermal energy-supply systems must not interfere



UTP GEN-A Page 4 of 7

Status: IN FORCE

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Date: 01.12.2011

OTIF UTP

Corresponding text in EU regulations 1

EU ref.

with the environment beyond the specified limits.

2.2.3 Technical compatibility

The electricity/thermal energy supply systems used must:

- enable trains to achieve the specified performance levels,
- in the case of electricity energy supply systems, be compatible with the collection devices fitted to the trains.

2.3 Control-command and signalling

2.3.1 Safety

The control-command and signalling installations and procedures used must enable trains to travel with a level of safety which corresponds to the objectives set for the network. The control-command and signalling systems should continue to provide for safe passage of trains permitted to run under degraded conditions.

2.3.2 Technical compatibility

All new infrastructure and all new rolling stock manufactured or developed after adop-

systems (CCS)" by the Committee of **Technical Experts**

the UTP "Control Command and Signalling | compatible control-command and signalling systems

must be tailored to the use of those systems.

The control-command and signalling equipment installed in the train drivers' cabs must permit normal operation, under the specified conditions, throughout the rail system.

2.4 Rolling stock

2.4.1 Safety

The rolling-stock structures and those of the links between vehicles must be designed in such a way as to protect the passenger and driving compartments in the event of collision or derailment.

The electrical equipment must not impair the safety and functioning of the controlcommand and signalling installations.

The braking techniques and the stresses exerted must be compatible with the design of the tracks, engineering structures and signalling systems.

Steps must be taken to prevent access to electrically-live constituents in order not to endanger the safety of persons.

In the event of danger devices must enable passengers to inform the driver and accompanying staff to contact him.

The access doors must incorporate an opening and closing system which guarantees passenger safety.

Emergency exits must be provided and indicated.

Appropriate provisions must be laid down to take account of the particular safety conditions in very long tunnels.

An emergency lighting system having a sufficient intensity and duration is an absolute requirement on board trains.

Trains must be equipped with a public address system which provides a means of communication to the public from on-board staff.



UTP GEN-A Page 5 of 7

Status: IN FORCE

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Date: 01.12.2011

OTIF UTP

Corresponding text in EU regulations 1

EU ref.

2.4.2 Reliability and availability

The design of the vital equipment and the running, traction and braking equipment and also the control and command system must, in a specific degraded situation, be such as to enable the train to continue without adverse consequences for the equipment remaining in service.

2.4.3 Technical compatibility

The electrical equipment must be compatible with the operation of the control-command and signalling installations.

In the case of electric traction, the characteristics of the current-collection devices must be such as to enable trains to travel under the energy-supply systems for the rail system

The characteristics of the rolling stock must be such as to allow it to travel on any line on which it is expected to operate, taking account of relevant climatic conditions.

2.4.4 Controls

Trains must be equipped with a recording device. The data collected by this device and the processing of the information must be harmonised.

2.5 Maintenance

2.5.1 Health and safety

2.5.1 The technical installations and the procedures used

in the centres

must ensure the safe operation of the subsystem and not constitute a danger to health and safety.

2.5.2 Environmental protection

The technical installations and the procedures used in the maintenance centres must not exceed the permissible levels of nuisance with regard to the surrounding environment.

2.5.3 Technical compatibility

The maintenance installations for rolling stock must be such as to enable safety, health and comfort operations to be carried out on all stock for which they have been designed.

2.6 Operation and traffic management

2.6.1 Safety

Alignment of the network operating rules and the qualifications of drivers and on-board staff and of the staff in the control centres must be such as to ensure safe operation, bearing in mind the different requirements of cross-border and domestic services.

The maintenance operations and intervals, the training and qualifications of the maintenance and control centre staff and the quality assurance system set up by the operators concerned in the control and maintenance centres must be such as to ensure a high level of safety.



UTP GEN-A Page 6 of 7

Status: IN FORCE

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Date: 01.12.2011

OTIF UTP

Corresponding text in EU regulations 1

EU ref.

2.6.2 Reliability and availability

The maintenance operations and periods, the training and qualifications of the maintenance and control centre staff and the quality assurance system set up by the operators concerned in the control and maintenance centres must be such as to ensure a high level of system reliability and availability.

2.6.3 Technical compatibility

Alignment of the network operating rules and the qualifications of drivers, on-board staff and traffic managers must be such as to ensure operating efficiency on the rail system, bearing in mind the different requirements of cross-border and domestic services.

2.7 Telematics applications for freight and passengers

2.7.1 Technical compatibility

The essential requirements for telematics applications guarantee a minimum quality of service for passengers and carriers of goods, particularly in terms of technical compatibility.

Steps must be taken to ensure:

- that the databases, software and data communication protocols are developed in a manner allowing maximum data interchange between different applications and operators, excluding confidential commercial data,
- easy access to the information for users.

2.7.2 Reliability and availability

The methods of use, management, updating and maintenance of these databases, software and data communication protocols must guarantee the efficiency of these systems and the quality of the service.

2.7.3 Health

The interfaces between these systems and users must comply with the minimum rules on ergonomics and health protection.

2.7.4 Safety

Suitable levels of integrity and dependability must be provided for the storage or transmission of safety-related information.

2.8 Other (movable) railway material

The EU regulations do not have this in its scope.

2.8.1 Safety

The structures of this railway material and the links between it and the vehicle, if carried, must be designed in such a way as to ensure that unintended move is prevented, even under emergency braking conditions and shunting.

Electrical equipment must not impair the safety and functioning of the control-command and signalling installations, be that of infrastructure installations or in trains.



UTP GEN-A Page 7 of 7

Status: IN FORCE

Version: 05

Ref.: A 94-01A/1.2011

Original: EN

Date: 01.12.2011

OTIF UTP

2.8.2 Technical compatibility

The characteristics of this railway material must be such as to allow it to travel on any line on which it is expected to operate, taking account of relevant climatic conditions.

2.8.3 Health

The staff and, if appropriate passengers, shall be protected against danger and inconvenience.

(End of document)

Corresponding text in EU regulations 1

EU ref.